

WB Rome (41')_19



	lulti ul 05 mL KEGEL
Tank Configuration ALT Tank A Conditioner KEGEL Tank B Conditioner start stop LOADS MICS SPEED BUFFER CROSSED START END FEET T.OIL 1 2 2 5 50 14 3 185 0.0 7.9 7.9 9250 2 5 50 14 3 31 7.9 9.8 1.9 1550 3 6L 6R 1 50 14 3 29 9.8 11.7 1.9 1450 450	KEGEL
START STOP LOADS MICS SPEED BUFFER CROSSED START END FEET T.OIL 1 2L 2R 5 50 14 3 185 0.0 7.9 7.9 9250 2 5L 5R 1 50 14 3 31 7.9 9.8 1.9 1550 3 6L 6R 1 50 14 3 29 9.8 11.7 1.9 1450	
1 2L 2R 5 50 14 3 185 0.0 7.9 9.250 2 5L 5R 1 50 14 3 31 7.9 9.8 1.9 1550 3 6L 6R 1 50 14 3 29 9.8 11.7 1.9 1450	
2 5L 5R 1 50 14 3 31 7.9 9.8 1.9 1550 3 6L 6R 1 50 14 3 29 9.8 11.7 1.9 1450	
3 6L 6R 1 50 14 3 29 9.8 11.7 1.9 1450	
5 8L 8R 1 50 14 3 25 15.6 17.5 1.9 1250	Π
6 9L 9R 2 50 18 3 46 17.5 22.6 5.1 2300	
7 10L 10R 1 50 18 3 21 22.6 25.1 2.5 1050 8 11L 11R 1 50 18 3 19 25.1 27.6 2.5 950	
9 12L 12R 1 50 18 3 17 27.6 30.1 2.5 850	1 11°3
10 2L 2R 0 50 22 3 0 30.1 33.0 2.9 0	
11 2L 2R 0 50 30 3 0 33.0 41.0 8.0 0	
	₩₩
START STOP LOADS MICS SPEED BUFFER CROSSED START END FEET T.OIL	
1 2L 2R 0 50 30 3 0 41.0 20.0 -21.0 0 2 13L 13R 1 50 26 3 15 20.0 16.4 -3.6 750	₽
3 11L 11R 1 50 22 3 19 16.4 13.3 -3.1 950	
4 9L 9R 1 50 18 3 23 13.3 10.8 -2.5 1150	H m
5 2L 2R 1 50 18 3 37 10.8 8.3 -2.5 1850	
6 2L 2R 0 50 14 3 0 8.3 0.0 -8.3 0	
	H 👷
	1 ≈
	⊥ ≈
	~
Cleaner Ratio Main Mix 5:1 Forward	
Cleaner Ratio Back End Mix 5:1 Reverse	
Cleaner Ratio Back End Distance 59 Combined	
Buffer RPM: 4 = 720 3 = 500 2 = 200 1 = 50	=
Item 3L-7L:18L-18R 8L-12L:18L-18R 13L-17L:18L-18R 18L-18R:17R-13R 18L-18R:12R-8R 18L-18R:7R-3R	
Description Outside Track:Middle Middle Track:Middle Inside Track:Middle MIddle: Inside Track Middle:Middle Track Middle:Outside Track	_

Description O	Outside Track:Middle	Middle Track:Middle	Inside Track:Middle	MIddle: Inside Track	Middle:Middle Track	Middle:Outside Track
rack Zone Ratio	2.57	1.27	1	1	1.27	2.57
1500 1300 1200 1050 900 750 600 450 300 150 0 1 2 2 3						